

## Standard Features

27" Bin Lid  
Remote Lid Opener

Roof Inspection Hole

5" Wall Corrugation

Double Bolted Vertical  
Seams

HPR Bin  
Mounting Ring

Powder Coated Cone

HSS (Hollow  
Structural Steel) Legs

Double or Triple Skid

## Hopper Types

35° One Piece Cones  
(15'- 21' Dia.)

35° Split Cones  
(24'-27' Dia.)



Manway

## Common Accessories

Roof Vents



LevAlert Indicator



Spiral Staircase

Ladder Cages



Fan Support Stand

## AirMax<sup>®</sup> Aeration



Horizontal Aeration



In-line Fans



Vertical Aeration



Centrifugal Fans



### Naming Conventions

**2406**

**24'**  
Bin Diameter

**6**  
Rings of Wall Sheets

### Contact Us Today

galvanized@meridianmfg.com | (800) 661-1436

Hopper Combo	Bushel Capacity	Bin & Cone Diameter	Overall Height (A)	Roof Height (B)	Wall Height (C)	Cone/Skid Height (D)	Bin Weight (LBS)	HPR Cone Weight (LBS)	Overall Weight (LBS)	Auger Requirement
1505 SC	3,342	15'	30'-8"	4'-5"	18'-11"	7'-4"	5,606	2,620	6,956	HD10-59 or SLMD10-66
1506 SC	3,909	15'	34'-5"	4'-5"	22'-8"	7'-4"	6,236	2,620	7,586	HD10-59 or SLMD10-66
1805 SC	4,874	18'	32'-11"	5'-1"	18'-11"	8'-6"	6,667	3,100	8,247	HD10-59 or SLMD10-66
1806 SC	5,690	18'	36'-8"	5'-1"	22'-8"	8'-6"	8,821	3,400	10,421	SLMD10-66
2105 SC	6,804	21'	35'-1"	6'-2"	18'-11"	9'-8"	8,930	4,660	11,530	SLMD10-66
2106 SC	7,914	21'	38'-10"	6'-2"	22'-8"	9'-8"	10,020	4,660	12,620	SLMD10-66
2406 SC	10,498	24'	41'-1"	7'-2"	22'-8"	10'-10"	13,513	7,300	15,963	SLMD10-66
2706 SC	13,643	27'	43'-5"	8'-3"	22'-8"	12'-1"	16,801	9,000	19,701	SLMD10-72

SC= Single Corrugated. Maximum bushel capacity based on grain peaked in roof area @ 27 degrees plus 5% compaction.

