



STANDARD FEATURES:

- 6-Feature Load Sensing Hydraulic Power System
- Wireless Remote with LCD Display
- 8 Inch x 24 Foot High Capacity Conveyor (824CHC)
- Premium Spool Tension Roll Tarp System
- 8" Conveyor w/ 12" Patented Meridian Cleated Belt
- Conveyor Inlet Canvas Cover
- Discharge Height up to 15ft
- Steep Angle Hopper Design
- GX340 Honda Engine w/ Electric Start and Battery Recharge
- Independent Scale Support Structure
- High Impact Bone White Powder Coat Finish
- Wired Master Control Box



TRAILER FEATURES:

- Torsion 7K Axles on Triple Axle Trailer -or- Gooseneck
- Electric Brakes
- Bolt-on Bumper Hitch or Gooseneck trailer
- 2 5/16 Ball Hitch Coupler
- Battery Break-away
- Wire harness w/ 7-pin Connector
- New High Impact Black Powder Coat Finish
- L.E.D. Lights

OPTIONS:

- Tri-axle bumper or gooseneck trailer
- Talc applicator
- 10" 2-tier spout
- 10" flex spout
- Quick-tach
- Auto-Convey™ scale



SPECIFICATIONS	4055
Overall Length	30'- 8-1/2"
Width	8' 5-3/4"
Height- floor to top of body	11'-5"
Maximum Discharge Height	14'-10"
Conveyor Spout Reach	19' - 6"
Tank Capacity	405 Units 321 Bushels